



Multikupplung 2-fach Bestellnummer: 56080, 56081

Datenblatt

PSQ2.1313.003 PAG. 1 of 4

INNESTO DI RICAMBIO
SPARE COUPLING POT4.1313.113

PARTE MOBILE MOBILE PART

PSQ2.1313.001 PAG. 3 of 4

AGGANCIO - CONNECTION

PARTE MOBILE MOBILE PART

PSQ2.1313.002 PAG. 2 of 4

INNESTO DI RICAMBIO
SPARE COUPLING POT4.1313.112

PARTE FISSA FIXED PART

PSQ2.1313.001

DATI TECNICI:
 N°2 INNESTI DN13 (ISO10)
 FILETTATURA INNESTI G1/2 UNI ISO 228/1 (GAS)
 PRESSIONE MASSIMA D'ESERCIZIO 250 Bar
 PORTATA NOMINALE 23 l/min
 TEMPERATURA D'ESERCIZIO Da -25°C a +125°C
 FATTORE DI SICUREZZA 4:1

TECHNICAL DATA:
 N°2 COUPLINGS DN13 (ISO10)
 COUPLINGS THREADS G1/2 UNI ISO 228/1 (BSP)
 MAX WORKING PRESSURE 250 Bar
 RATED FLOW 23 l/min
 WORKING TEMPERATURE FROM -25°C TO +125°C
 SAFETY FACTOR 4:1

PARTE MOBILE INNESTABILE
CON PRESSIONE RESIDUA

MOBILE PART CONNECTABLE
UNDER RESIDUAL PRESSURE

Flow Rate (Q) [l/min]	Flow Rate (Q) [US/GPM]	Pressure Drop (ΔP) [bar]	Pressure Drop (ΔP) [PSI]
11.5	3	~0.5	~7.25
23	6	~1.0	~14.5
34.5	9.1	~1.5	~21.75
46	12.1	~2.0	~29.0
57.5	15.2	~3.0	~43.5